

Kształtowniki z/g gat. S235JR oraz S355J2H

Profile kwadratowe

Rozmiar	Grubość ścianki (s) mm														
	1,25	1,5	2,0	2,5	3,0	4,0	5,0	6,0	7,0	8,0	10,0	12,0	12,5	16,0	20,0
(a)	Waga teoretyczna (kg/m)														
(mm)															
10		0,355													
12		0,449													
15	0,508	0,59	0,736												
20	0,704	0,826	1,05	1,25	1,42										
25	0,901	1,06	1,36	1,64	1,89										
30	1,10	1,30	1,68	2,03	2,36	2,94	3,42								
35	1,29	1,53	1,99	2,42	2,83	3,57									
40	1,49	1,77	2,31	2,82	3,30	4,20	4,99								
45	1,69	2,00	2,62	3,21	3,77	4,83	5,77								
50	1,88	2,24	2,93	3,60	4,25	5,45	6,56	7,56							
60	2,27	2,71	3,56	4,39	5,19	6,71	8,13	9,45	10,30	11,30					
70	2,67	3,18	4,19	5,17	6,13	7,97	9,70	11,30	12,50	13,80	16,10				
80		3,65	4,82	5,96	7,07	9,22	11,30	13,20	14,70	16,40	19,30	20,80			
90			5,45	6,74	8,01	10,50	12,80	15,10	16,90	18,90	22,40				
100			6,07	7,53	8,96	11,70	14,40	17,00	19,10	21,40	25,60	28,30			
110					9,90	13,00	16,00	18,90	21,30	23,90	28,70	32,10			
120					10,80	14,20	17,50	20,7	23,50	26,40	31,80	35,80			
130					11,80	15,50	19,1	22,60	25,70	28,90	35,00	39,60			
140					12,70	16,80	20,70	24,50	27,90	31,40	38,10	43,40			
150					13,70	18,00	22,30	26,40	30,10	33,90	41,30	47,10			
160					14,60	19,30	23,80	28,30	32,30	36,50	44,40	50,90			
175					16,00	21,20	26,20	31,1	35,60	44,20	49,10	56,60			
180					16,50	21,80	27,00	32,10	36,70	41,50	50,70	58,50	60,50		
200					18,40	24,30	30,10	35,80	41,10	46,50	57,00	66,00	68,30		
220					20,30	26,80	33,20	39,60	45,50	51,50	63,20	73,50	76,20		
250							38,00	45,20	52,10	59,10	72,70	84,80	88,00		
260								47,10		61,60	75,80		91,90		
280								50,90	58,70	66,60	82,10	96,10	99,73	124,01	
300								54,70		71,60	88,40		108,00	134,00	
320								58,43		76,65	94,64		115,43	144,10	174,92
350									64,08	84,20	104,00		127,00	159,00	193,76
400										96,75	120,00		147,00	184,00	225,16
500											151,16		186,08	234,54	287,96