

Kształtowniki z/g gat. S235JR oraz S355J2H

Rury

| Wymiar | | Grubość ścianki (s) mm | | | | | | | | | | | | | |
|------------|--------|-------------------------|-------|------|------|------|------|------|-------|-------|-------|-----|-------|----|----|
| (Średnica) | | 1.5 | 2.0 | 2.5 | 3.0 | 4.0 | 5.0 | 5.6 | 6.0 | 6.35 | 7.0 | 7.1 | 8.0 | 10 | 12 |
| (mm) | (cale) | Waga teoretyczna (kg/m) | | | | | | | | | | | | | |
| 12 | | 0,388 | | | | | | | | | | | | | |
| 14 | | 0,462 | | | | | | | | | | | | | |
| 15 | | 0,499 | 0,641 | | | | | | | | | | | | |
| 16 | | 0,536 | 0,691 | | | | | | | | | | | | |
| 17,2 | 3/8" | | 0,75 | | | | | | | | | | | | |
| 18 | | 0,610 | 0,789 | | | | | | | | | | | | |
| 20 | | 0,684 | 0,888 | | | | | | | | | | | | |
| 21,3 | 1/2" | 0,732 | 0,952 | 1,16 | 1,35 | 1,71 | | | | | | | | | |
| 22 | | 0,758 | 0,986 | | | | | | | | | | | | |
| 25 | | 0,869 | 1,13 | 1,39 | 1,63 | | | | | | | | | | |
| 26,9 | 3/4" | 0,940 | 1,23 | 1,50 | 1,77 | 2,26 | | | | | | | | | |
| 28 | | 0,980 | 1,28 | 1,57 | 1,85 | | | | | | | | | | |
| 30 | | 1,05 | 1,38 | 1,70 | 2,00 | 2,56 | | | | | | | | | |
| 32 | | 1,13 | 1,48 | 1,82 | 2,15 | | | | | | | | | | |
| 33,7 | 1" | 1,19 | 1,56 | 1,92 | 2,27 | 2,93 | 3,45 | | | | | | | | |
| 35 | | 1,24 | 1,63 | 2 | 2,37 | 3,06 | | | | | | | | | |
| 38 | | 1,35 | 1,78 | 2,19 | 2,59 | 3,35 | | | | | | | | | |
| 40 | | 1,42 | 1,87 | 2,31 | 2,74 | 3,55 | 4,32 | | | | | | | | |
| 42,4 | 1"1/4 | 1,51 | 1,99 | 2,46 | 2,91 | 3,79 | 4,61 | | | | | | | | |
| 45 | | 1,61 | 2,12 | 2,62 | 3,11 | 4,04 | | | | | | | | | |
| 48,3 | 1"1/2 | 1,73 | 2,28 | 2,82 | 3,35 | 4,37 | 5,43 | | | | | | | | |
| 50 | | 1,79 | 2,37 | 2,93 | 3,48 | 4,54 | 5,55 | | | | | | | | |
| 56 | | 2,02 | 2,66 | 3,30 | 3,92 | | | | | | | | | | |
| 57 | | 2,05 | 2,71 | 3,36 | 4,00 | 5,23 | 6,41 | | | | | | | | |
| 60,3 | 2" | 2,18 | 2,88 | 3,56 | 4,24 | 5,55 | 6,82 | 8,03 | | | | | | | |
| 63,5 | | | 3,03 | 3,76 | 4,48 | 5,87 | 7,21 | 8,51 | | | | | | | |
| 70 | | 2,53 | 3,35 | 4,16 | 4,96 | 6,51 | 8,01 | 9,47 | | | | | | | |
| 76,1 | 2"1/2 | 2,76 | 3,65 | 4,54 | 5,41 | 7,11 | 8,77 | 9,74 | 10,40 | 10,92 | 11,90 | | 13,40 | | |
| 80 | | 2,90 | 3,85 | 4,78 | 5,70 | 7,50 | 9,25 | | 10,90 | | 12,60 | | 14,20 | | |
| 83 | | 3,01 | 4,0 | 4,96 | 5,92 | 7,79 | 9,62 | | 11,40 | | 13,10 | | 14,80 | | |

| Wymiar | | Grubość ścianki (s) mm | | | | | | | | | | | | | |
|------------|--------|-------------------------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--------|
| (Średnica) | | 1.5 | 2.0 | 2.5 | 3.0 | 4.0 | 5.0 | 5.6 | 6.0 | 6.35 | 7.0 | 7.1 | 8.0 | 10 | 12 |
| (mm) | (cale) | Waga teoretyczna (kg/m) | | | | | | | | | | | | | |
| 88,9 | 3" | 3,23 | 4,29 | 5,33 | 6,36 | 8,38 | 10,30 | 11,50 | 12,30 | 12,93 | 14,10 | | 16,00 | 19,50 | 22,80 |
| 101,6 | 3"1/2 | | 4,91 | 6,11 | 7,29 | 9,63 | 11,90 | | 14,10 | | 16,30 | | 18,50 | 22,60 | 26,50 |
| 108 | | | 5,23 | 6,50 | 7,77 | 10,30 | 12,70 | | 15,10 | | 17,40 | | 19,70 | 24,20 | 28,40 |
| 114,3 | 4" | | 5,54 | 6,89 | 8,23 | 10,90 | 13,50 | 15,01 | 16,00 | 16,91 | 18,50 | 18,77 | 21,00 | 25,70 | 30,30 |
| 121 | | | 5,87 | 7,31 | 8,73 | 11,50 | 14,30 | | 17,00 | | 19,70 | | 22,30 | 27,40 | 32,30 |
| 127 | 4"1/2 | | 6,17 | 7,68 | 9,17 | 12,10 | 15,00 | | 17,90 | | 20,70 | | 23,50 | 28,90 | 34,00 |
| 133 | | | 6,46 | 8,05 | 9,62 | 12,70 | 15,80 | | 18,80 | | 21,80 | | 24,70 | 30,30 | |
| 139,7 | 5" | | | | 10,10 | 13,40 | 16,60 | 18,52 | 19,80 | 20,88 | 22,90 | 23,22 | 26,00 | 32,00 | 37,80 |
| 141,3 | 5" | | | | 10,23 | 13,40 | 16,81 | 18,74 | | 21,13 | | 23,50 | | | |
| 152,4 | | | | 9,24 | 11,10 | 14,60 | 18,20 | | 21,70 | | 25,10 | | 28,50 | 35,10 | 41,50 |
| 159 | | | 7,74 | 9,65 | 11,50 | 15,30 | 19,00 | | 22,60 | | 26,20 | | 29,80 | 36,70 | |
| 168,3 | 6" | | | | 12,20 | 16,20 | 20,10 | 22,47 | 24,00 | 25,36 | 27,80 | 28,23 | 31,60 | 39,00 | 46,30 |
| 177,8 | | | | | 12,90 | 17,10 | 21,30 | | 25,40 | | 29,50 | | 33,50 | 41,40 | 49,10 |
| 193,7 | | | | | 14,10 | 18,70 | 23,30 | | 27,80 | | 32,20 | | 36,60 | 45,30 | 53,80 |
| 219,1 | 8" | | | | 16,00 | 21,20 | 26,40 | | 31,50 | | 36,60 | | 41,60 | 51,60 | 61,3 |
| 273 | 10" | | | | 20,00 | 26,50 | 33,00 | | 39,50 | | 45,90 | | 52,30 | 64,90 | 77,20 |
| 323,9 | 12" | | | | | | 39,30 | | 47,00 | | 54,70 | | 62,30 | 77,40 | 92,30 |
| 355,6 | 14" | | | | | | 43,20 | | 51,70 | | 60,20 | | 68,60 | 85,20 | 102,00 |
| 406,4 | 16" | 4.50 - 17.50 mm | | | | | | | | | | | | | |
| 426,0 | | 4.80 - 17.50 mm | | | | | | | | | | | | | |
| 457,2 | 18 | 4.80 - 20.00 mm | | | | | | | | | | | | | |
| 508,0 | 20 | 5.60 - 20.00 mm | | | | | | | | | | | | | |
| 530,0 | | 5.60 - 20.00 mm | | | | | | | | | | | | | |
| 558,8 | 22 | 6.30 - 20.00 mm | | | | | | | | | | | | | |
| 609,6 | 24" | 7.10 - 20.00 mm | | | | | | | | | | | | | |